


DFM1722S25EA

Center Frequency[fo]	1722.5MHz
Bandwidth[BW]	±12.5MHz
Insertion Loss in BW	2.5dB max.
Ripple in BW	1.0 dB max.
VSWR in BW	1.5: 1max.
Attenuation [Absolute Value]	50.0min.@1817MHz
In/Out Impedance	50Ω
Input Power	1 w max.
Operation Temperature	-40℃ ~ +85 ℃



DFM172252SEA

Tr1: S11 Log Mag 5.000dB/ Ref 0.000dB [F2]
 Tr2: S21 Log Mag 10.00dB/ Ref 0.000dB [F2]
 Tr3: S22 Log Mag 5.000dB/ Ref 0.000dB [F2]

10.00
 0.000
 -10.00
 -20.00
 -30.00
 -40.00
 -50.00
 -60.00
 -70.00
 -80.00
 -90.00

1 1.7100000 GHz -26.435 dB
 2 1.7220000 GHz -28.254 dB
 3 1.7350000 GHz -22.590 dB
 4 1.8170000 GHz -0.4292 dB
 1 1.7100000 GHz -1.4182 dB
 2 1.7220000 GHz -1.3811 dB
 3 1.7350000 GHz -1.4771 dB
 4 1.8170000 GHz -55.551 dB
 1 1.7100000 GHz -22.777 dB
 2 1.7220000 GHz -22.090 dB
 3 1.7350000 GHz -24.466 dB
 4 1.8170000 GHz -0.4681 dB

Tr1: Pass
 Tr2: Pass
 Tr3: Pass
 Rn12: Pass 36.190 mdB

1 Center 1.7225 GHz IFBW 70 kHz Span 300 MHz Cor